

WHAT IS CLAIMED IS:

1. A communication path setting method of setting a communication path between a first telephone terminal system
5 connected to a packet network and a second telephone terminal system connected to a circuit switching network and said circuit switching network, wherein said packet network and said circuit switching network are connected through a gateway device which performs predetermined signal conversion,

10 said second telephone terminal system being provided with a first port connected to said packet network and a second port connected to said circuit switching network, said communication path setting method comprising:

a step (A) in which said first control device receives a
15 connection request for connecting said second telephone terminal system from said first telephone terminal system;

a step (B) in which said first control device transmits said connection request to said second control device through said packet network;

20 a step (C) in which said second control device determines whether or not said first port is operating in response to said connection request; and

a step (D) in which, when it is determined in said step (C) that said first port is not operating, said second control
25 device sets said communication path through said packet network, said circuit switching network and said second port by the use of said gateway device.

2. The communication path setting method as claimed in claim 1
30 further comprising:

a step (E) in which said first control device determines, through said packet network, whether or not said second control device is operating in response to said connection request; and

35 a step (F) in which, when it is determined in said step (E) that said second control device is not operating, said first control device sets said communication path through said packet network, said circuit switching network and said second port by the use of said gateway device.

3. The communication path setting method as claimed in claim 1 wherein said second control device sets, in said step (D), said communication path by the use of said gateway device
5 which is associated with said second control device.

4. The communication path setting method as claimed in claim 2 wherein said first control device sets, in said step (F), said communication path by the use of said gateway device which is
10 associated with said first control device.

5. The communication path setting method as claimed in one of claims 1 through 4 further comprising a step of notifying to said first telephone terminal system whether said packet
15 network alone or both said packet network and said circuit switching network is used as a route through which said communication path is set.

6. A communication path setting system that sets a
20 communication path between a first telephone terminal system connected to a packet network and a second telephone terminal system connected to a circuit switching network and said circuit switching network, wherein said packet network and said circuit switching network are connected through a gateway
25 device which performs predetermined signal conversion,

said second telephone terminal system is provided with a first port connected to said packet network and a second port connected to said circuit switching network,

said first control device comprising:

30 a receiving unit that receives a connection request for connecting said second telephone terminal system from said first telephone terminal system; and

a request transmitting unit that transmitting said connection request to said second control device through said
35 packet network,

said second control device comprising:

a first determination unit that determines whether or not said first port is operating in response to said connection request; and

a first setting unit that sets said communication path through said packet network, said circuit switching network and said second port by the use of said gateway device when said first determination unit determines that said first port
5 is not operating.

7. The communication path setting system as claimed in claim 6 wherein said first control device comprises:

a second determination unit that determines, through
10 said packet network, whether or not said second control device is operating in response to said connection request; and

a second setting unit that sets said communication path through said packet network, said circuit switching network and said second port by the use of said gateway device when
15 said second determination unit determines that said second control device is not operating.

8. The communication path setting system as claimed in claim 6 wherein said first setting unit sets said communication path
20 by the use of said gateway device which is associated with said second control device.

9. The communication path setting system as claimed in claim 7 wherein said second setting unit sets said communication path
25 by the use of said gateway device which is associated with said first control device.

10. The communication path setting system as claimed in one of claims 6 through 9 further comprising a notification unit that notifies to said first telephone terminal system
30 whether said packet network alone or both said packet network and said circuit switching network is used as a route through which set said communication path is set.